

70-200-HC SERIES

Bronze Solder x 3/4" Hose Connection With Cap & Chain

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

DESCRIPTION

The Apollo® 70200HC Series is ideally suited for direct connection to hoses. Valve contains a securely attached cover with chain which prevents damage to hose threads.

FEATURES

- Stainless Steel Lever and Nut
- Blow-Out-Proof Stem Design
- Adjustable Packing Gland
- RPTFE Seats and Stuffing Box Ring
- Cap & Chain protects hose thread
- Heavy brass cap is full pressure rated
- Stainless Steel Reversed Handle
- Solder End x ¾" NPSH
- Manufactured and 100% Factory Tested in the USA

PERFORMANCE RATING

- Maximum Pressure: 600 psi CWP
- Vacuum Service to 29 in. Hg

MODELS

70-240-HC Series

316 SS Ball & Stem

STANDARD MATERIALS LIST

Part Name	Material
Lever and Grip	Stainless Steel w/ Vinyl
Stem Packing	MPTFE
Stem Bearing	RPTFE
Ball	B16, Chrome Plated
Seat (2)	RPTFE
Retainer	B16 Brass
Gland Nut	B16 Brass
Stem	B16 Brass
Lever Nut	Stainless Steel
Body	B584-C84400 Bronze


APPROVALS

 MSS SP-110; Ball Valves Threaded, Socket-Welding, Solder Joint, Grooved and Flared Ends



DIMENSIONS

PART #	SIZE	Α	В	С	D	E	F	G	Н	WT
70203HC	1/2"	0.50	1.42	3.08	3.32	1.94	4.18	0.63	0.5	0.71
70204HC	3/4"	0.68	1.93	3.84	4.09	2.32	5.31	0.88	0.75	1.44
70205HC	1"	0.87	2.25	4.49	4.73	2.43	5.31	1.13	0.9	2.13



OPTIONS

(-03) 1 1/4" CS Stem Extension	1/2" - 1"
(-04) 2 1/4" CS Stem Extension	1/2" - 1"
(-07) Steel Tee Handle	1/2" - 1"
☐ (-11) Therma-Seal™ Insulating Tee Handle	1/2" - 1"
(-15) Wheel Handle, Steel	1/2" - 1"
(-27) SS Latch-Lock Lever & Nut	1/2" - 1"
(-93) 1-1/4" Extension w/ Balancing stop	1/2" - 1"
(-94) 2-1/4" Extension w/ Balancing stop	1/2" - 1"
☐ 70-240-HC Series - 316 SS Ball & Stem	1/2" - 1

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28106 USA; www.apollovalves.com; 704-841-6000