



Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

## DESCRIPTION

The Apollo<sup>®</sup> 95LF series is a full port stop and waste ball valve ideal for plumbing or hydronic systems where draining is required. Features a heavy pattern dezincification resistant Lead Free\* bronze body.

#### **FEATURES**

- Lead Free\* Brass & Bronze Materials .
- Drain Port with Finger Tight Shut-off
- 1/2" through 1" Sizes, NPT & Solder •
- Easily Identifiable Blue "Lead Free" Hang Tag
- Adjustable Stem Packing Nut •
- 100% Made in the USA.

#### PERFORMANCE RATING

- Maximum Rated Pressure: 400 psi CWP
- Maximum Working Temperature: 120°F
- Suitable for water and non-hazardous fluids

### MATERIALS SPECIFICATION

Part Name	Material
Lever and Grip	Steel, Zinc Plated w/ Vinyl
Stem Packing	RPTFE
Stem Bearing	RPTFE
Ball	C27450, Lead Free* Brass, Chrome.Plated
Seat (2)	RPTFE
Retainer	C27450, Lead Free*
Gland Nut	B16 Brass
Stem	C27450, Lead Free*
Lever Nut	Steel, Zinc Plated
Body	C89836, Lead Free*, Bronze

### **APPROVALS**

- MSS SP-110; Ball Valves Threaded, Socket-Welding, Solder Joint, Grooved and Flared Ends
- ANSI/NSF 61-8 2008, Annex F & G, 0.25% Lead max

## **OPTIONS**

- (-04) 2-1/4" Stem Extension
- (-07) Steel Tee Handle
- ☐ (-11) Therma-Seal<sup>™</sup> Insulating Tee Handle ☐ (-27) SS Latch-Lock Lever & Nut
- (-94) 2-1/4" Extension Kit with Balancing Stops

Consult factory for availability of LF model options

\*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with CA AB 1953 and VT S.152. ANSI 3rd party certified and listed

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28106 USA; www.apollovalves.com; 704-841-6000


This specification is provided for reference only. Conbraco reserves the right to change any portion of this specification without notice and without incurring obligation to






# DIMENSIONS

Part #	Size	Α	В	С	D	Ε	F	G	Wt. (lbs.)		
NPT											
95LF10301	1/2"	0.50	1.54	3.08	1.50	3.87	0.53	-	0.63		
95LF10401	3/4"	0.75	1.78	3.55	2.01	4.87	0.74	-	1.39		
95LF10501	1"	1.00	1.93	3.86	2.20	4.87	0.81	-	1.90		
SOLDER											
95LF20301	1/2"	0.50	1.43	2.87	1.75	3.87	0.76	0.50	0.70		
95LF20401	3/4"	0.75	2.12	4.12	2.15	4.87	1.04	0.75	1.53		
95LF20501	1"	1.00	2.21	4.43	2.43	4.87	1.21	0.91	1.90		





E

