

LEAD FREE*

Model 102T-LF CLASS 125 GATE VALVE

NON RISING STEM, NPT

(30LF SERIES)

Job Name:

Contractor:

Job Location:

P.O. Number:

Engineer:

Representative:

Wholesale Distributor:

Description

The **Lead-Free*** Apollo Model 102T-LF (30LF Series) Gate Valve provides a "Made in the USA" alternative to globally sourced multi-turn valves for potable water service. These valves are cast, machined, assembled, and tested in South Carolina using proven ASTM quality materials.

Features

- Lead-Free* ANSI 3rd Party Certified
- Full Port design
- Guided Solid Bronze Disc
- · Adjustable Graphite Stem Packing
- · Non-Rising Stem
- NPT Connection
- · Screw-in Bonnet
- Rugged Malleable Iron Hand Wheel
- · Back seat protection
- 100% Factory tested
- · Cast, Machined and Assembled in the USA
- ARRA Compliant

Standards

MSS SP-139, "Copper Alloy Bronze Gate, Globe, Check Valves"

NSF/ANSI 61-8, Annex G

NSF 372 Lead Free* ANSI 3rd Party Certified

ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"

CSA B51 CRN 0C14667.5

Performance Rating

CWP: 200 psi (13.8 Bar) at 100°F SWP: 125 psi (8.6 Bar) at 353°F Temperature Range: -20°F to 406°F

* LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with CA AB1953, VT Act 193, MD HB372, LA HB471 and Federal Public Law 111-380.

Ordering Information

Model	Item Number		
102T14-LF	30LF-031-01		
102T38-LF	30LF-032-01		
102T12-LF	30LF-033-01		
102T34-LF	30LF-034-01		
102T1-LF	30LF-035-01		
102T114-LF	30LF-036-01		
102T112-LF	30LF-037-01		
102T2-LF	30LF-038-01		
102T212-LF	30LF-039-01		
102T3-LF	30LF-030-01		
	102T14-LF 102T38-LF 102T12-LF 102T34-LF 102T1-LF 102T114-LF 102T112-LF 102T2-LF		





Material Specifications

material operations				
Material				
ASTM B584-C89836 Bronze				
ASTM B584-C89836 Bronze				
ASTM B371-C69400 Bronze				
ASTM B584-C89836 Bronze				
Grafoil®				
ASTM B16 Brass				
Malleable Iron				
Aluminum				

Physical Specifications

Size	Height (open) In.	Length (in.)	Weight (Lbs)	Cv** (gpm)
1/4"	3.29	1.76	.74	3.0
3/8"	3.29	1.76	.71	6.0
1/2"	3.56	2.03	.85	12.5
3/4"	4.05	2.07	1.19	24.0
1"	4.55	2.45	1.98	72.3
1-1/4"	5.14	2.63	2.8	80.0
1-1/2"	6.02	2.88	3.95	119.0
2"	7.09	3.06	5.88	338.0
2-1/2"	9.11	4.13	12.19	395.0
3"	12.61	4.48	16.84	435.0

^{**} Cv = flowrate at 1.0 psid.





Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA; www.apollovalves.com; 704-841-6000