

Model 161T CLASS 125 SWING CHECK

	BRONZE SEAT, NPT	
	(61Y SERIES)	
Job Name:	Contractor:	
Job Location:	P.O. Number:	
Engineer:	Representative:	
Tag:	Wholesale Distributor:	

Description

The Apollo Model 161T Swing Check provides a cost effective "made in the USA" alternative to globally sourced check valves. These valves are cast, machined, assembled, and tested in South Carolina. The Apollo Swing Check can be installed in both horizontal or vertical line with upward flow.

Features

- Renewable Seat Disc
- Metal Seat
- Dezincification Resistant
- 100% Factory tested
- NPT Connection
- 100% machined and assembled in USA

Standards

- MSS SP-80, "Bronze Gate, Globe & Check Valves"
- ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"

Performance Rating

Saturated Steam: 125 psi (8.6 Bar) to 353°F(178°C) Cold Working Pressure: 200 psi (13.8 Bar) at 100°F Temperature Range: -20°F to 406°F

Order Information

Size	Model	Item Number Thread (NPT)
1/4"	161T	61Y-191-01
3/8"	161T	61Y-192-01
☐ ¹ ⁄2"	161T	61Y-193-01
☐ ³ ⁄4"	161T	61Y-194-01
□ 1"	161T	61Y-195-01
<u></u> 1-1/4"	161T	61Y-196-01
□ 1-½"	161T	61Y-197-01
2"	161T	61Y-198-01
2-1/2"	161T	61Y-199-01
3"	161T	61Y-190-01



Material Specifications

Material				
ASTM B62 Bronze				
ASTM B62 Bronze				
304 Stainless Steel				
304 Stainless Steel				
ASTM B62 Bronze				
ASTM B16 Brass				

Dimensions

Size	Height	Length	Weight	Cv
	(in.)	(in.)	(lbs)	(gpm)
1/4"	1.51	2.14	.64	2.6
3/8"	1.51	2.14	.62	4.5
1/2"	1.65	2.48	.73	7.0
3/4"	1.9	2.94	1.1	12.0
1"	2.26	3.57	1.7	28.6
1-1/4"	2.99	4.50	3.4	39.0
1-1/2"	2.99	4.50	3.1	56.0
2"	3.74	5.25	5.5	152.0
2-1/2"	5.11	8.00	11.7	198.0
3"	6.05	9.24	17.8	242.0



Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000

Conbraco Industries can accept no responsibility for possible errors in this document and reserves the right to alter its product design or construction without notice and without incurring any obligation to make such changes on Conbraco products previously or subsequently sold. All product specifications are approximate and are provided for reference only.