

69BV SERIES PIPE MASTER™ Ball Valve

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

DESCRIPTION

The new Apollo[®] PIPEMASTER™ ball valve is a universal full port ball valve designed for virtually any residential or commercial plumbing application. Various end connections to make over 100 possible combinations.



FEATURES

- Adjustable Stem Packing
- Full-Port Flow
- Fast, Easy, Economical Installation
- Blow-Out Proof Stem Design
- Corrosion Resistant Materials
- All Popular Connection Options
- Silicone Free

PERFORMANCE RATING

- Temperature Rating: 32°F to 210°F
- Valve Body is Rated 600 CWP
- Actual Maximum Pressure Rating Limited by Connection Pipe Adapter. See below.

APPROVALS


- MSS SP-110 Ball Valves
- ANSI/NSF 61-8 (61<5) Potable Water
- ASTM F1807 Standard Specification for Metal Insert Fittings Utilizing a Copper Crimp Ring for SDR9 Cross linked Polyethylene (PEX) Tubing
- Directive 2002/95/CE (RoHS) Compliant

MATERIAL SPECIFICATIONS

Part Name	Material
BODY	BR0NZE
LEVER	STEEL, ZINC PLATED W/ VINYL GRIP
STEM PACKING	
STEM BEARING	MPTFE
BALL	BRASS, CHROME PLATED
SEAT	MPTFE
RETAINER	BRASS
O-RING	EPDM
GLAND NUT	BRASS
STEM	BRASS
LEVER NUT	STEEL, ZINC PLATED

CENTER SECTION

Center Section	Size	ize Dimensions (in.)			Wt.	Carton
Part Number	(in.)	Α	В	C	(lbs.)	Qty.
69BV0301PZ	1/2"	1.82	2.00	4.78	0.7	20
69BV0401PZ	3/4"	2.31	2.15	5.67	1.2	30
69BV0501PZ	1"	2.68	2.38	6.16	1.7	10



PIPE ADAPTER

*Sold separately from Center Section assembly.

69BV - Size - Pipe Adapter - PZ

Size : ☐ 03 = ½"	04 = ¾"	□ 05 = 1"
Pipe Adapter:	NUMBER	PRESSURE RATING
SOLDER	(02)	200 CWP
☐ MALE NPT	(03)	600 CWP
☐ FEMALE NPT	(04)	600 CWP
☐ PVC	(05)	200 CWP
☐ CPVC	(06)	400 CWP
☐ PEX	(07)	200 CWP
☐ COMPRESSIO	ON (08)	200 CWP
□ PUSH	(09)	200 CWP
PE (POLY)	(10)	200 CWP

Example: 69BV-04-02-PZ - 3/4" Solder adapter

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28106 USA; www.Apollovalves.com; 704-841-6000